

4, 8, 16channel SDI HD DVR



4CH:



8CH:



16CH:



Features:

- > With H.264 compression, smaller stream, higher quality, longer recording time.
- > With unique front panel and time screen,
- > Support Symbian S60V3/V5, Windows Mobile, Iphone, Android, Blackberry mobile view.
- > Support 4sata HDD (2TB), 2 USB(2.0) interface for backup, burning, upgrading operation
- > Stronger network service, support IE browse and CMS software
- > Support Chinese, Russian, English, Italian, Portuguese, Spanish, French, German 30 language
- > Build-in 3322.org, dyndns.net, oray.net and myq-see.com free DDNS dynamic domain name
- > **With HDMI, Support 1080P the high-definition (1920 * 1080P)**
- > **Support P2P function, no network limitation, and no need to set the router..**

	Model	ST-HD-DVR6004 4ch	ST-HD-DVR6008 8ch	ST-HD-DVR6016 16ch
System	Main processor	HI3531 chip		
	Screen display	1/4	1/4/8/9	1/4/8/9/16
Video	Video standard	1080P@30fps(SMPTE 292); PAL (625TVL, 50Fields / sec.); NTSC (525TVL, 60 Fields / sec.)		
	Video quality	Monitor : D1; VGA: HD; HDMI: HD		
	Coding capacity	4ch 1080p realtime	8ch 720p realtime	16ch 720p realtime
	Decoding capacity	1ch 1080p realtime	1ch 720p realtime	4ch 720p realtime
	Motion Detection	Each screen can be set to 192 (16 × 12) detection area; multi-level sensitivity can be set		
Video playback	Recording Mode	Manual> Alarm> Motion detection> timing		
	Playback	Single,		
	Search Mode	Point-in-time retrieval, calendar search, event search, channel search		
Storage backup	Space Occupation	CIF: 5G / day / channel D1: 20G / day / channel 720P: 40G / day /channel 1080P: 80 G/ day/channel		
	Video storage	HDD. Network		
	Backup Mode	Network backup、USB mobile HDD、USB Burner, DVD CD burning		

Interface	Video input	4ch HD-SDI	8ch HD-SDI	16ch HD-SDI
	Video output	1ch BNC output, 1ch spot output, 1ch VGA output, 1ch HDMI output(support 1920*1080P)		
	Audio input	4CH RCA	8CH RCA	16CH RCA
	Audio output	1 ch RCA output		
	Alarm input	16 ch alarm input		
	Alarm output	4 ch		
	Net interface	RJ45 10M/100M/1000M		
	PTZ control	RS485		
	USB interface	2 *USB interface		
	Hard Disk	4*SATA interface (biggest 3TB for each)		
Others	Power Supply	12V/8A External power supply		
	Dimension	430 (width) x380 (deep) x65 (high) mm		
	Weight	8kg (not including HDD)		