

Model No.: **GSM-TIT-670**



### Features:

- Based on GSM 900/1800MHz
- Support **reverse polarity**
- Can connect to **PBX**
- With LiOn-battery, support standby time over 48hours
- With 2x RJ11 phone ports, can be connect with extension

### Main Functions:

1. Suitable for GSM 900/1800MHz using SIM card
2. Making & answering calls after connecting to telephone set
3. Available to connect with telephone set, Billing machine, etc
4. Supports the functions of redialing and hands-free
5. Voice adjustment of calling in and out, multi-lever volume to be chosen
6. Caller ID
7. Featured with signal intensity indicator, working status indicator, breakdown indicator, etc
8. Built-in PIN code protection featured with locking device/card/network

### Technique Parameters:

- Working Frequency
  - Rx (EGSM 900): 925~960MHz
  - Tx (EGSM 900): 800~915MHz
  - Rx (DCS 1800): 1805~1880MH
  - Tx (DCS 1800): 1710~1785MHz
- Power Consumption: <=5W
- Working Voltage: DC12V
- User Access Port:
  - Dialing tone frequency: 450Hz continued
  - Busy tone frequency: 450Hz 0.35s/0.35s

### Package Information:

Size: 181(L) x 125(W) x 35 (H)mm

Weight: 290g